



POLYCAB INDIA LIMITED

Industrial Cables LP No. 07/2018-19 Dtd : 9th January 2019

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT LEAD FREE (FRLF) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - HEAT RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE CONFORMING TO IS-694:2010 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FRLF						HR	
	45 Mtr.	Coils Per Box	90 Mtrs.	Coils Per Box	180 Mtrs. (Box Packing)	Coils Per Box	90 Mtrs.	Coils Per Box
0.75	395	48	785	28			825	28
1	510	36	1020	24	2040	12	1070	24
1.5	765	30	1525	16	3050	10	1600	16
2.5	1230	20	2455	12	4910	6	2580	12
4	1835	16	3665	8	7330	4	3855	8
6	2745	8	5490	6	10980	3	5765	6
10			9700	1				
16			15530	1				

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – FLAME RETARDANT LEAD FREE (FRLF) / FLAME RETARDANT LOW SMOKE (FRLSH) CONFORMING TO IS-694:2010 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – FLAME RETARDANT ZERO HALOGEN (FRZH) / LOW SMOKE ZERO HALOGEN (LSZH) / HALOGEN FREE FLAME RETARDANT (HFFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - HEAT RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE CONFORMING TO IS-694:2010 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FRLF		FRLS-H		FRZH/LSZH/HFFR		HR	
	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	180 Mtrs. (Pouch Packing)	Coils Per Box
0.75	2615	10	2745	10	2810	10		
1	3400	8	3570	8	3655	8	2140	12
1.5	5085	6	5340	6	5465	6	3200	10
2.5	8185	4	8595	4	8800	4	5160	6
4	8145	4	8550	4	8755	4	7710	4
6	12200	3	12810	3	13115	3	11530	3
10	21555	1	22635	1	23170	1		
16	34510	1	36235	1	37100	1		

Notes

- The above rates are exclusive of GST which shall be charged extra.
- This Price List is subject to change without notice.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.