

CR652B LED Cleanroom

**LED CLEAN
ROOM**

Ashesh Kumar Dasgupta





CR652B LED Cleanroom



USP

- ❖ Efficacy ~ 90 Lm/W
- ❖ < 40% energy saving Vs Conventional
- ❖ CRI > 80
- ❖ SDCM < 3.5
- ❖ Front Opening

Specifications

- CRCA housing with single piece CRCA frame
- Lumen Pack : 3300/ 5600 Lm
- System Power : 36W/60W
- Life : L70 , 50K Hrs
- IP 65 with Toughened Glass
- IP 54 with Clear Acrylic
- Suitable for front Opening Application





Technical Specification

Parameter	CR652B LED33S CR CW GT	CR652B LED33S CR NW CA	CR652B LED56S CR CW GT	CR652B LED56S CR NW CA
System Wattage	33	33	56	56
Lumen Output	3300	3300	5600	5600
System Efficacy	<90	<90	<90	<90
Color Temperature	6500	4000	6500	4000
CRI	80			
THD	< 10 for 3300 Lumen and < 20 for 5600 Lumen			
PF	<.9			
IP	IP 65	IP 54	IP 65	IP 54
Housing	White Powder Coated CRCA steel			
Frame	Single Piece white powder coated CRCA frame			
Mounting	Recessed			
Access for Maitainance	Bottom Opening			
Reflector	High reflective white power coated CRCA Steel			
Cover	Toughened Glass	Clear Acrylic	Toughened Glass	Clear Acrylic

